

Pack 3894 Pinewood Derby 2011 – Guidelines & Rules

The Pinewood Derby is open to all Cub Scouts. **Cars should be built by the Cub Scouts with some adult guidance.** Any technical assistance should be fully explained to the Cub Scout so that he can use that knowledge on future projects. The intent is for the Adult to do as little as possible. Adult mainly do the cutting of the block of wood. Let the boy design the car and do as much of final carving (age appropriate with knife—Tiger & and some Wolves should not whittle), rough & final sanding, paint job, etc. Wheel assembly should be done by the parent for younger boys to ensure wheels go in straight.

Specifications

Maximum width - 2-3/4"

Maximum Length - 7"

Maximum Weight - Not over 5 Ounces

Minimum width between wheels - 1-3/4

Minimum bottom clearance underneath the body (so it does not rub on the track guide) - 3/8"

RULES

Wheel bearings, washers, and bushings are prohibited. The car shall not ride on springs. Only official Cub Scout Grand Prix Pinewood Derby wheels and axles are permitted (The kits provided to you). Only dry lubricant is permitted. Details, such as steering wheel and driver are permissible as long as these details do not exceed the maximum length, width and weight specifications. The car must be free-wheeling, with no starting devices. Each car must pass inspection by the official inspection committee before it may compete. If, at registration., a car does not pass inspection, the owner will be informed of the reason for failure, and will be given time within the official weigh-in time period to make the adjustment. After final approval, cars will not be re-inspected unless the car is damaged in handling or in a race.

BUILDING INSTRUCTIONS

Check the grooves to ensure that each is at a perfect 90-degree angle to the car body. A car with untrue axles tends to steer to one side or the other, causing it to rub up against the side of the lane strip, slowing it down. You can check the groove angles by using a square, a protractor, or even a piece of paper.

Lay square on block to check for squareness and alignment of slot.

Use two hacksaw blades side by side to redress the slots. Use the edge of the square as a guide.

Choose your favorite design, then mark the block accordingly (See Figure 1). Lay car body on the side, then gently drive the axles into the grooves within 1/4" of the axle head. Axles should fit tight. With a pair of pliers, remove axles by pulling and turning gradually (See Figure 2). Repeat on the other side of block. Most of the cutting can be done with a hand saw, then finished with sandpaper (See Figure 3).

Details such as fins and scoops should be added now. Any additional weight needed to achieve a total of 5 ounces should be built into the car.

NOTE: If the car design you chose has a narrow body, make sure the area where the axles are inserted into the body remains 1-3/4" wide, or wheels will not fit over the guide strips of the track.

PAINTING AND WHEEL ASSEMBLY

Apply several coats of sanding sealer; then sand entire car with a fine-grade sandpaper. Give model at least two coats of fast drying paint, in your choice of color. When paint is completely dry sand with a

fine sandpaper, apply a final coat of paint and allow to dry thoroughly. To finish, rub entire car with a rubbing compound. Details such as windshield, driver, racing numbers, etc., should be added now. For a super finish apply a coat of auto wax and rub to a high gloss. Pre-lubricate axles and wheels using, **dry powdered lubricant**. Do not use regular oil or silicone spray, since it may soften the plastic. Slide wheels over axles, then gently tap them into the car body grooves with a 1/4" dowel or similar object to within 1/32" of car body. (See Figure 4). Make sure wheels turn freely.

---reference official handout © Copyright 1997 Boy Scouts of America

VERY IMPORTANT ADDITIONAL RULES

- Use only Official BSA Pinewood Derby Kit wood, wheels, and nails. (Other wheels & kits are available on the internet are NOT to be used)
- **Wheels may only be lightly sanded to smooth out molding imperfections in the tread area. Beveling, tapering, thin sanding, wafering, of the wheels is prohibited. The decorative dots on the wheel treads may not be removed. Lathe Turning is ok, but not "excessive".** In other words, the Cub Scouts should be able to do all this themselves with Adult directions.
- **Wheel Axles may be lathe turned but not "excessive".** In other words, the Cub Scouts should be able to do all this themselves with Adult directions.
- Motors, engines, or other propulsion may not be used.
- The Minimum Front Nose Width shall be at least 0.5" and parallel with the front axle to operate properly on the track. Cars must be no more than 3.5" high to fit under the finish gate.
- **Previous Years Cars are prohibited from Racing; only 2011 Models allowed.**
- **Right before Weigh-In, you'll be allowed to do apply your final Dry lubricant; however there will be no further application between heats.**